

POWER ACCESSORIES

2P 16A Air Breaker C Curve 6kA DIN Rail Mount

Model DELIXI DZ47s-C16



High-performance 2P 16A air breaker for industrial distribution panels. Features 6kA breaking capacity and C curve. Ideal for solar control systems and OEMs.

Features

- 2P16A Air Breaker
- Rated Current: 16A
- Breaking Capacity: 6kA/10kA
- Frequency: 50/60Hz
- Electrical Life: > 10,000
- Application: Suitable for solar, control, distribution, and industrial panels
- Poles: 2P
- Rated Voltage: 400V AC
- Tripping Curve: C Curve
- Mechanical Life: > 20,000
- Mounting: DIN rail mount

Specification

Model	DELIXI DZ47s-C16
Rated Current (In)	16A
Number of Poles / Voltage	2P / 400V
Tripping Curve	Type C
Breaking Capacity	6kA, compliant with IEC/EN 60898-1
Frequency	50 / 60 Hz
Protection Performance	Overload protection, short circuit protection, isolation control
Operating Temperature	-35°C to +70°C
Storage Temperature	-40°C to +85°C
Installation Height	Up to 2000 m above sea level
Protection Level	IP20
Installation	Standard 35 mm DIN rail



Contact us

Maxsol South Africa

Website

<https://maxsol-tech.co.za>

Phone

+86 19849790018

Email

sales@maxsol-tech.com

Service area

South Africa

Address

5/F, Bangshen Lixinhu Technology Industrial Park, No. 132 Dayang Road, Fuhai Subdistrict, Bao'an District, Shenzhen, China

Facebook

LinkedIn

WhatsApp