

NETWORK SWITCH

24-Port Fast Ethernet PoE+ Switch with Gigabit Uplinks

Model PS12402FE-L

24-port Fast Ethernet PoE+ switch with 2 Gigabit RJ45 uplinks, 1 SFP slot, 300W power supply, VLAN isolation, Extend mode and PoE watchdog.

Features

- 24FE+2GE+1GF Uplink Lite Series 300M Long Range PoE Switch
- Internal power adapter supply 300W
- Support AI network self-healing (watchdog) function
- Plug and Play, no configuration requirements
- 6KV surge protection function
- IEEE 802.3af/at compliant, up to 30 W per PoE port
- Support DIP switch to VLAN / Extend 300M / Watchdog
- Support desktop and wall-mounted, and rack-mount installation
- Metal case, internal power supply, excellent heat dissipation performance for long-term stable operation

Specification

Interfaces

Model	PS12402FE-L
Fixed Port	24*10/100Base-TX PoE ports (Data/Power) 2*10/100/1000Base-T RJ45 ports (Data) 1*100/1000Base-X uplink SFP fiber slot (Data)
Network Protocol	IEEE802.3 10BASE-T; IEEE802.3i 10Base-T; IEEE802.3u 100Base-TX/FX; IEEE802.3ab 1000Base-T; IEEE802.3z 1000base-X; IEEE802.3x.
Ethernet Port Feature	10/100Base-T(X) 10/100/1000 Base-T automatic detection, full/half Duplex MDI/MDI-X adaptive
Fiber Port Feature	Gigabit SFP Port (Fiber module is not included, need to order separately, module options include single/multi-mode, single/dual fiber, LC)
Forwarding Mode	Store and Forward

PoE

POE Port	Port 1-24 support PoE @ IEEE802.3af/at
Feature	With the Dial code switch, E: AI Extend 300meters transmission; V: Turn on, 1-24 Port support each port Isolation & VLAN; Support Watchdog function by default: 1-24 Port support AI-PoE Network self-healing mode (PoE Watchdog function), Automatic solve the camera problem & reduce after-sale. W: Turn on, 1-24 Port support AI-PoE Network self-healing mode (PoE Watchdog function), Automatic solve the camera problem & reduce after-sale.
Fan	Non-Fan, silent working status can satisfy more users with different requirement.
PoE Standard	IEEE802.3af/at

Switch Property

Switching Capacity	10.8Gbps (non-blocking)
Forwarding Mode	8.05Mpps
MAC address table	8K
Buffer Memory	4M
Twisted Pair Transmission	10BASE-T: Cat5 UTP (≤300 meter) 100BASE-TX: Cat5 or later UTP (≤100 meter) 1000BASE-T: Cat5 or later UTP (≤100 meter)
Power Supply Pin	Default 1/2(+), 3/6(-)
MAX / AVERAGE Power Per Port	30W/15.4W
Total PWR / Input Voltage	300W (100-240V)
Power Consumption	Standby: <5W Full load: <300W

Physical Characteristics

LED Indicator	Power indicator: PWR (Green) Network indicator: 1-24(Link/Act) / (Green), 25-27(Link/Act) / (Green)
Power Supply	Built in switching power supply, AC100~240V 50-60Hz 4.1A
Operation TEMP / Humidity	-20~+55°C:5%~90% RH non condensing
Storage TEMP / Humidity	-40~+75°C:5%~95% RH non condensing
Dimension	310*205*44mm
Net /Gross Weight	Net: <2.5kg Gross: <3kg
Installation Method	desktop type, wall mounted, 19-inch 1U cabinet installation
Protection	IEC61000-4-2(ESD): ±8kV contact discharge, ±15kV air discharge IEC61000-4-5(Lightning protection/Surge): Power:CM±4kV/DM±2kV; Port: ±6kV

Protection Level	IP30
------------------	------

Certification

Certification	CE, FCC, RoHS
---------------	---------------

Package Contents

Switch	1 pcs
Power cord	1 pcs
Hanging Ears	1 pcs
Quick installation guide	1 pcs



Contact us

Maxsol South Africa

Website

<https://maxsol-tech.co.za>

Phone

+86 19849790018

Email

sales@maxsol-tech.com

Service area

South Africa

Address

5/F, Bangshen Lixinhu Technology Industrial Park, No. 132 Dayang Road, Fuhai Subdistrict, Bao'an District, Shenzhen, China

Facebook

LinkedIn

WhatsApp