

NETWORK SWITCH

4-Port Hi-PoE Switch with VLAN and Extend Mode

Model PS1402E



4-port Hi-PoE switch with 300-meter transmission and a 65W power budget, featuring VLAN, AI Watchdog, and up to 60W output on the Hi-PoE port.

Features

- 4FE+2FE Uplink HiPoE 300M Long Range PoE Switch
- Port 4 supports Hi-PoE power up to 60W fit IEEE 802.3bt compliant PDs
- Support VLAN
- Supports smart watchdog function to monitor compliant PD
- Port 1-3 supports PoE 30W fit IEEE 802.3af/at compliant PDs
- Internal power adapter supply 65W (included)

Interfaces

Model	PS1402E
Fixed Port	4*10/100Base-T/TX PoE ports (Data/Power) 2*10/100Base-T/TX Uplink RJ45 ports (Data)
Network Protocol	IEEE802.3 10BASE-T; IEEE802.3i 10Base-T; IEEE802.3u 100Base-TX; IEEE802.3x.
Ethernet Port Feature	10/100Base-T(X) automatic detection, full/half Duplex MDI/MDI-X adaptive
Fiber Port Feature	Store and Forwards

PoE

PoE Port	Port 1-4 support PoE
Feature	With the Dial code switch, support port priority by default. E: AI Extend 300meters transmission and auto speed change of single port (limit 10Mbps), other ports maintain 100M/1000M within 100 meters; V: Turn on, 1-4 Port support each port Isolation & VLAN; W: Turn on, 1-4 Port support AI-PoE Network self-healing mode (PoE Watchdog function), Automatic solve the camera problem & reduce after-sale.

Switch Property

Switching Capacity	1.2Gbps
Forwarding Mode	0.89Mpps
MAC address table	2K
Buffer Memory	768K
Twisted Pair Transmission	10BASE-T:Cat5 UTP(≤300 meter) 100BASE-TX:Cat5 or later UTP(≤100 meter)
Power Supply Pin	Default 1/2(+), 3/6(-)
MAX power each port	Port 1-3 30W, port 4 60W
Total PWR / Input Voltage	65W (52VAC)
Power Consumption	Standby: <2W Full load: <65W

Physical Characteristics

LED Indicator	Power indicator: PWR (Green); Network indicator: 1-4(Link/Act) / (Green), 5-6(Link/Act) / (Green),
Power Supply	Build-in power adaptor AC100~240V 50-60Hz, 65W
Operation TEMP / Humidity	-20~+55°C: 5%~90% RH non condensing
Storage TEMP / Humidity	-40~+75°C: 5%~95% RH non condensing
Dimension	195*130*40mm
Net /Gross Weight	Net: <0.8kg Gross: <1.2kg
Installation Method	desktop type, wall mounted
Protection	IEC61000-4-2(ESD): ±8kV contact discharge, ±15kV air discharge IEC61000-4-5(Lightning protection/Surge): Power: CM±4kV/DM±2kV; Port: ±4kV
Protection level	IP30

Certification

Certification	CE, FCC, RoHS
---------------	---------------

Package Contents

Switch	1 pcs
Power cord	1 pcs
Quick installation guide	1 pcs



Contact us

Maxsol South Africa

Website

<https://maxsol-tech.co.za>

Phone

+86 19849790018

Email

sales@maxsol-tech.com

Service area

South Africa

Address

5/F, Bangshen Lixinhu Technology Industrial Park, No. 132 Dayang Road, Fuhai Subdistrict, Bao'an District, Shenzhen, China

[Facebook](#)

[LinkedIn](#)

[WhatsApp](#)